

HOT AIR CURTAIN

*A robust and low noise fan.
Ideally suited for use in shops, offices,
supermarkets...
In summer, it doubles as a air circulation fan.
It matches any decoration thanks to its nice design.
Ceiling or wall mounting*



Technical specifications:

- 2 ratings / 2 speeds
- Silent tangential fans.
- Polyester coated zinc steel.
- White colour with black fins.
- Built-in overheat safety cut-out with manual reset
- Built-in power relays and connection terminal.

2 executions :

2000 / 4000 W : with built-in controls
temperature adjustment button
2 buttons : stop - 2000 w
full speed - reduced speed – stop
other models : to be connected to a remote control

Accessories:

- remote control ref, 3497-1 : On/Off button + full/stop/half heating + full/reduced speed (can drive up to 4 units)
- thermostat, ref 3497-2: adjustment of the temperature
- Must be wired with a 3 core cable (live, neutral, earth).
- Class I, Drip-proof, IP 21, IK 08.
- Voltages : 4000/2000 w model : 230 V single phase
other models : 230 V single phase or 230 V 3 phases or 400 V + neutral 3 phases

reference	ratings W	length mm	height mm	thickness mm	temperature increase °C.	airflow m3 / hour	tensions amp.	weight kg
with built-in controls								
3403-1	4000/2000	690	205	150	37,5/23,5	300/240	17,3	8,4
to be connected to a remote control								
3403-2	6000/3000	890	205	150	37,5/23,5	450/350	26,1/15,1/8,7	12
3404-1	4500/2250	1100	270	205	7/11	980/1270	19,6/11,3/6,5	20
3404-2	9000/4500	1100	270	205	13,5/21	980/1270	26,1/15,1/8,7	20
3404-3	9000/4500	1550	270	205	12/17	1100/1600	26,1/15,1/8,7	30
3404-4	12000/6000	1550	270	250	16/22	1100/1600	52,2/30,1/17,3	30

Maximum installation height :
up to 2 m for the 4000/2000 w and 6000/3000 w models
up to 3 m for the other models